



Product Code

Description

Technical Data

Storage

FLOOR GRAPHICS

Embossed, scuff resistant, clear soft vinyl.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

Overlaminating film designed for production of FLOOR TALKERS (TM) , indoor floor graphic advertising.

FACE MATERIAL

Type	Plasticised vinyl film
Colour and Finish	Clear
Weight	260g/m ²
Thickness	200μ

ADHESIVE

Reference	RI-ASP8A
Type	Permanent acrylic
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/ +140°C
Shear	Excellent
Tack	Medium
Ultimate Adhesion	Very high

RELEASE BACKING

Type	1 side siliconised glassine
Colour and Finish	White
Weight	90g/m ²
Thickness	77μ
Transparency	>32%

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.