



Product Code

RI-JET 205

Description

Gloss clear plasticised vinyl film, with good flexibility and conformability to curved surfaces.

Printing methods: solvent and UV inkjet.

Permanent adhesive with very good adhesion on glass and on a wide variety of substrates, except for apolar (PE, PP).
BGVV compliance (indirect food contact)

For promotional graphics and point of sale advertising with medium outdoor durability (ca. 3 years).

Technical Data

FACE MATERIAL

Type	Plasticised vinyl film
Colour and Finish	Clear
Weight	110g/m ²
Thickness	80µ

ADHESIVE

Reference	RI - AP
Type	Permanent acrylic
Min. Appl. Temp.	+10°C
Service Temp.	-30°C / +120°C
Cohesion	Excellent
Tack	Medium
Ultimate Adhesion	High

RELEASE BACKING

Type	1 side silicone coated kraft
Colour and Finish	White
Weight	135g/m ²
Thickness	135µ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.
The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.